

'2 3/\$66,,&,&25(&7,),(56

<p>) HDWXUHV</p> <p>"Plastic package has Underwrites Laboratory</p> <p>) ODPPELOLW\ & ODVVLILFDWLRQ 9</p> <p>"Fast switching speed</p> <p>"Diffused junction</p> <p>"High current capability</p> <p>"High temperature soldering guaranteed: 250¢ /10 seconds, 0.375"(9.5mm)lead length,5lbs.(2.3kg)tension</p> <p>" & DVH - ("2& PRO SHOD E WGF</p> <p>" 3 RODUL W D & SHORR DHWKH R G H</p> <p>" ORXQWR Q U WLRQ \$ Q \</p>	
--	--

0\$;,080 5\$7,1*6 \$1' &+\$5\$&7(5,67,&6

f & \$ PELH W SHUDX Q Q R H W K H U Z R L W H G

			%\$	%\$	%\$
7<3(180%(5					
0D[LPXP UHSHWLWLYH SHDN UHYH 95/50 YROWDJH	9506	9			
0D[LPXP 506 YROWDJH	9506	9			
0D[LPXP ' & EORFNLQJ YROWDJH	9' &	9			
	,) \$9	\$			
)60	\$			
2SHUDWLQJ MXQFWLRQ WHP SHUDWXUH UDQJH				WR	
6WRUDJH WHP SHUDWXUH UDQJH	7VWJ			WR	
0D[LPXP LQVWDQWDQHRXV IRUZDUG YROWDJH DW \$				0D[
			\$	0D[0D[LPXP B	