

FEATURES

Ideal for printed circuit board

Reliable low cost construction utilizing molded plastic technique

Plastic material has U/L flammability classification 94V-O

		GBU 15A	GBU 15B	GBU 15D	GBU 15G	GBU 15J	GBU 15K	GBU 15M	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward output current T _c =100°C	$I_{F(AV)}$				15.0				A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}				240.0				A
Maximum instantaneous forward voltage at 7.5 A	V_F				1.0				V
Maximum reverse current @T _A =25°C at rated DC blocking voltage @T _A =125°C	I_R				5.0 500.0				μA mA
Typical junction capacitance per leg (note 3)	C_J		211				94		pF
Typical thermal resistance per leg (note 2)	$R_{\theta JA}$				21.0				°C/W
(note 1)	$R_{\theta JC}$				2.2				
Operating junction temperature range	T_J				- 55 ---- + 150				°C
Storage temperature range	T_{STG}				- 55 ---- + 150				°C

NOTE: 1. Unit case mounted on 3.2x3.2x0.12" thick (6.2x8.2x0.3cm) Al. Plate.

2. Units mounted in free air, no heat sink on P.C.B., 0.5x0.5"(12x12mm) copper pads, 0.375"(9.5mm) lead length.

3. Measured at 1.0 MHz and applied reverse voltage of 4.0 volts.

