

Üæcä} \*Äc [ÄF€€€XÄÜÜX

Ü \* ! \* ÄÄ [ç^i] [æäÄtæcä} \*Äc [ÄH€€€€ { ] ^! ^Ä] ^æ\ÄÄQä^æ|Ä- [ iÄ] iä) c^äÄ&äi & ~ äcÄä [æiä

ä) Ää} ^ø ] ^) •äç^Ä] ! [ ä ~ & cÄÄŠ^æäÄ • [ |ä^!æä|Ä] ^!ÄTÜŠËÜVÖËG€Ä { ^c@ [ äÄG€i

		KBPC 25005	KBPC 2501	KBPC 2502	KBPC 2504	KBPC 2506	KBPC 2508	KBPC 2510	UNITS
Maximum recurrent peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum average forward Output current @ $T_A=25^\circ\text{C}$	$I_{F(AV)}$	25.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	$I_{FSM}$	300.0							A
Maximum instantaneous forward voltage @ 12.5 A	$V_F$	1.1							V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	$I_R$	10.0 1.0							A mA
Operating junction temperature range	$T_J$	- 55 ---- + 125							$^\circ\text{C}$
Storage temperature range	$T_{STG}$	- 55 ---- + 150							$^\circ\text{C}$

