

GCH!&'`

Pä* @ÄÖÖÄ&~!!^}cÄ*æä}KÄ@ØØKF€€EHG€È
 Š[, Ä•æc~ iæcä[]ÄÇ[]cæ*^È
 Û~âcæà|^Ä-[]Äâ:âÇ^iÄ•cæ*^Ä[-Ä• { æ||Ä { [c]iÈ
 Ô[{]|^ { ^}cæ:~Äc [ÄSVQ€FGJ]iÈ
 Û { æ||Ä]æ&\æ*^È

NPN Silicon Epitaxial Planar Transistor

Low frequency power amplifier application.

Power switching application.

A97<5B=75@ 85H5

Ôæ•^Ä•c^|^KÛUVÈGHÄ { []â^âÄ]|æ•cä&

T [~ }cä } *Ä] [•âcä []Kæ } ^

Symbol	Parameter	Value	Units
V _{CB0}	Collector-Base Voltage	35	V
V _{CE0}	Collector-Emitter Voltage	30	V
V _{EB0}	Emitter-Base Voltage	5	V
I _C	Collector Current -Continuous	800	mA
I _B	Base Current	160	mA
P _C	Collector Power Dissipation	200	mW
T _J , T _{stg}	Junction and Storage Temperature	-55 to +150	

F5H-B; S' 5B8' 7<5F57H9F=G#7' 7I FJ9G

