





5 \$ 7 , 1 \* 6 \$ 1 ' & + \$ 5 \$ & 7 ( 5 , 6 7 , & & 8 5

ÇVceMGÍ»ÔÁ~ }|^••Á[c@^!\_ î•^Á• ]^&î-î^âD

**Electrical characteristics (T<sub>j</sub>= 25°C)**

			-	1.35		V
		I <sub>F</sub> =6A, T <sub>j</sub> =175°C		1.50		
		V <sub>R</sub> =650V, T <sub>j</sub> =25°C	-	0.018	30	FA
		V <sub>R</sub> =650V, T <sub>j</sub> =150°C		1.2	120	FA
		V <sub>R</sub> =650V, T <sub>j</sub> =175°C	-	3.6	-	FA
		V <sub>R</sub> =1V, f=1MHz		300		pF
		V <sub>R</sub> =650V, f=1MHz	-	27	-	pF
	Q <sub>C</sub>	V <sub>R</sub> =400V, di/dt=350A/µs	-	19	-	
					-	ns
						mJ
Thermal resistance	R <sub>th(j-c)</sub>		-	4.2	4.9	°C/W

5 \$ 7 , 1 \* 6 \$ 1 ' & + \$ 5 \$ & 7 ( 5 , 6 7 , & & 8 5



5 \$ 7 , 1 \* 6 \$ 1 ' & + \$ 5 \$ & 7 ( 5 , 6 7 , & & 8